

MV: AMSTEL CONFIDENCE

General

Class	NKK
Class notation	BCM BC-XII, GRAB
Ship type	DHBC
Year built	NOV 2011
Yard	Minaminippon Shipyard, Japan
DD due	OCT 2019
SS due	NOV 2021

Flag	Portugal
Registry	Madeira
Reg. nr.	TEMP590M
Call Sign	CQAL4
IMO nr.	9623659
Telex	425501974
Phone	+870 77322 5571
Email	amstelconfidence@gtmailplus.com

Speed & Consumption

Laden	abt. 13.0 kts on abt. 26.0 IFO + abt. 0.1 mt MDO
Eco (WOG)	abt. 12.0 kts on abt. 21.0 IFO + abt. 0.1 mt MDO
Port Idle	abt. 2.0 mt IFO + abt. 0.1 mt MDO
Port WWW	abt. 4.2 mt IFO + abt. 0.1 mt MDO

Vessel consumes MDO when manoeuvring and sailing in narrow waterways and canals. Speed/Cons. upto Windforce BF 4/ Douglas sea state 3 and basis no adverse currents.
Bunker specs: IFO ISO 8217:2017 (E) RMG 380 / MDO: ISO 8217:2017 (E) DMB or DMA
However sulphur specs and each delivery and burning of specific types (grades) of bunkers always to comply with MARPOL regulations a/o EU directives a/o USA a/o any other national regulations including latest amendments.

Principal dimensions

Length over all	183.00	m
Breadth moulded	29.50	m
Depth moulded	15.00	m
Summer draft	10.366	m
Summer dwt	38,503	MT
TPC (summer)	48.7	t/cm
GT/NT	24020/12015	T
Lightweight	8329	T
Suez Gross/Nett	TBA	T
Panama PC/UMS	TBA	T

WL-H/c Summer	TBA	m
WL-H/c Ballast mid.	TBA	m
Keel – Top H/c	TBA	m
Keel – Top of mast	41.62	m
IFO capacity (85%)	1354	m ³
MDO capacity (85%)	359	m ³
MGO capacity (85%)		m ³
FW capacity (100%)	541	m ³
Ballast cap. (100%)	16032	m ³
Slop tanks (CH wash)	422	m ³

Operational restrictions

No mixing of new bunkers with bunkers already onboard.
Vessel is only allowed to work single hook on a single hatch
Constants could be affected due to vessel retaining onboard of hold cleaning water and/or grey water as per MARPOL regulations.

Bunker tank capacities could be affected due to vessel having to keep different IFO and MGO grades separated as a consequence of compliance with Marpol regulations a/o EU directives a/o USA a/o any other national regulations including latest amendments.

This vessel is member of an independent fuel testing system (LINTEC).
Charterers or their representatives are always at liberty to witness the sampling during any bunkering of the vessel under the charter and any discrepancies found between suppliers sample and Lintec sample then the Lintec sample to be final and binding. As long as the Lintec test of the HFSO onboard has not been completed and the results approved vessel may have to use LSFO or MDO/MGO instead

Cargospaces

Cap. (ft ³)	Grain	Bale
C/H #1	174802	170317
C/H #2	384258	375200
C/H #3	382359	375313
C/H #4	391975	384700
C/H #5	366725	360746
Total	1700119	1666276

Floor space	LxBf/Ba/H(m)	Hatch Size
C/H #1	TBA	11.20x17.00
C/H #2	29.60x25.00	21.60x25.00
C/H #3	29.60x25.00	21.60x25.00
C/H #4	29.60x25.00	21.60x25.00
C/H #5	TBA	21.60x25.00

drft(m)	Deadweight
10.36	Summer 38503
10.58	Trop. 39560
10.82	TropF. 39538
10.60	Fresh 38506
10.15	Winter 37449

Ventilation	Nat.
Airchanges	-
CO2 fitted	Fitted
A60 bkhd	N/A
Smoke det.	N/A
Aussie fitted	Fitted
Dehumidifier	N/A

*Note: In case of heavy cargoes to be loaded, the maximum quantity is to be in accordance with vessel's loading and stability booklets.

Strength

	CH#1	CH#2	CH#3	CH#4	CH#5		
Hatchcovers	N/A	N/A	N/A	N/A	N/A	t/m ³	*observe load manual
Weatherdeck	N/A	N/A	N/A	N/A	N/A	t/m ³	*Except betw. hatches
Tanktop						t/m ³	*Local strength
Tanktop	21	21	21	21	21	t/m ³	*Uniform distributed
Steel Coils	Standard coil loading condition - 2 tiers x 25 T coils (dim. W2.0m x L2.2m) 3 dunnages.						
*Note: Alternate hold loading condition (Nos. 2 & 4 may be empty)							
*Note 2: Other coil loading conditions subject to owners approval of local stress calculations.							

Deck equipment

Hatch type	Hydr. End-folding type, DS
Maker	MacGregor
Cargo gear type	Electr/hydr. 30t x 26m x 4 sets
Maker	Mitsubishi Heavy Industries
Outreach	11.25 mtr
Grab handling	24t max.
Grabs fitted	N/A

Features

ITF fitted	National flag
Log fitted	No
WBTS fitted (AMS approved)	No
Lakes fitted	No
Suitable for grab discharge	Yes

Machinery details

Main engine	Mitsui MAN B&W 6S50MC-C
NCO	6715 KW @ 114.6 rpm
Aux. engines	Yanmar 6 EY18L – 3 sets
Electrical	
Freshwater generator	Max. 20t/day

All details "about" given in good faith, without guarantee.